

NT1

Incredibly Quiet 1" Cardioid Condenser Microphone

RØDE
MICROPHONES




Features

- Large capsule (1") with gold-plated membrane
- Cardioid polar pattern
- Internal Rycote® Lyre® based capsule shock mounting system
- Ultra-low noise transformerless circuitry
- State-of-the-art surface mount electronics
- Heavy-duty matte black finish
- Gold plated output connectors
- Designed & manufactured in Australia
- Available with RM2 mount (NT1-SINGLE) or with SMR shock mount (NT1-KIT)
- Free 10 year extended warranty*


Specifications

Acoustic Principle	Pressure Gradient
Active Electronics	JFET impedance converter with bipolar output buffer
Directional Pattern	Cardioid
Frequency Range	20Hz ~ 20kHz
Output Impedence	100Ω
Equivalent Noise	4.5 dBA SPL (as per IEC651)
Maximum Output	+8 dBu (1kHz, 1% THD into 1K Ω load)
Sensitivity	-29 dB re 1V/Pa (35mV @ 94dB SPL) ± 2dB @ 1kHz
Dynamic Range	128 dB SPL
Maximum SPL	132 dB SPL
Signal / Noise	90 dBA SPL (as per IEC651)
Power Requirements	24V phantom power 48V phantom power
Output Connection	3 Pin XLR Balanced output between pin 2 (+), pin 3 (-) and pin 1 (ground)
Net Weight	395g

Polar Pattern



Frequency Response



www.rodemic.com

*After online registration

Australia
107 Carnarvon st, Silverwater NSW 2128 Australia
Ph: +61 2 9648 5855 Fx: +61 2 9648 2455

USA
PO Box 91028, Long Beach CA 90809-1028
Ph: +1 562 364 7400 Fax: +1 888 412 4664