

# 4-Port HDMI Switch

## VS481B

The VS481B 4-Port HDMI Switch allows you to quickly connect 4 HDMI sources to your HDMI display and easily switch between them via front panel pushbuttons, RS-232 or IR remote control. The front panel's LEDs indicate the source device selected for the display at a glance.


The VS481B supports Ultra HD 4Kx2K, the newest resolution for high definition displays; Auto Switching modes for auto port selection; Instant Switching for a smooth video transition between HDMI ports with increased efficiency; and features a built-in bi-directional RS-232 serial port that allows the switch to be controlled through a high-end controller, PC, and/or home automation/home theater software package.



### Features

- Allows up to four HDMI A/V sources to be connected to one HDMI display
- Quick and easy switching between HDMI sources via front panel pushbuttons, RS-232 or IR Remote control
- Supports 340MHz bandwidth for ultra high 4kx2k video
- HDMI (3D, Deep Color, 4kx2k); HDCP compatible
- Auto switching modes for auto port selection
- Long distance transmission – up to 15 m (24 AWG)
- Consumer Electronics Control (CEC) support
- Supports Dolby True HD and DTS HD Master Audio
- Built-in bi-directional RS-232 serial remote port for high-end system control
- Instant switching between HDMI input sources
- Supports IR extension using a IR extension cable\*
- LED indication of video source devices

**Note:** The IR extension cable (Part No. 2XRT-0003G) is not included in this package.



### Specifications

	VS481B
<b>Video Input</b>	
Interface	4 x HDMI Type A Female (Black)
Impedance	100 Ω
Max. Distance	3 m
<b>Video Output</b>	
Interface	1 x HDMI Type A Female (Black)
Impedance	100 Ω
Max. Distance	15 m
<b>Video</b>	
Max. Data Rate	9 Gbps (3 Gbps Per Lane)
Max. Pixel Clock	300 MHz
Compliance	HDMI (3D, Deep Color, 4K); HDCP 2.2 Compatible Consumer Electronics Control (CEC)
Max. Resolution	Up to 4096 x 2160 / 3840 x 2160 @ 60Hz (4:2:0); 4096 x 2160 / 3840 x 2160 @ 30Hz (4:4:4)
Max. Distance	Up to 15 m
<b>Audio</b>	
Input	4 x HDMI Type A Female (Black)
Output	1 x HDMI Type A Female (Black)
<b>Control</b>	
RS-232	<b>Connector:</b> 1 x DB-9 Female (Black) <b>Baud Rate and Protocol:</b> <b>Baud Rate:</b> 19200, <b>Data Bits:</b> 8, <b>Stop Bits:</b> 1, <b>Parity:</b> No, <b>Flow Control:</b> No
IR	1 x Mini Stereo Jack Female (Black)
<b>Power</b>	
Connectors	<b>Connector:</b> 1 x DC Jack; <b>Consumption:</b> 5 VDC, 5W
Consumption	5 VDC, 5W
<b>Environmental</b>	
Operating Temperature	0 - 50°C
Storage Temperature	-20 - 60°C
Humidity	0 - 80% RH, Non-Condensing
<b>Physical Properties</b>	
Housing	Metal
Weight	0.48 kg
Dimensions (L x W x H)	20.00 x 8.25 x 2.50 cm

Product information is subject to change without prior notice.

### ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datung Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com

Released: 06/2021 V3.0

© Copyright 2021 ATEN® International Co. Ltd.  
 ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.  
 The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

