



Input/Output	8P shielded cable
Input	Unidirectional condenser microphone
Operating Voltage	DC24V (supplied by the host)
Current Consumption	42mA
Sensitivity	-55Db
Signal-to-Noise Ratio	72dB
Microphone Current Induction	-42dB±5.1dB
Frequency Response	90-11KHZ
Installation Method	Desktop type
Connection Cable	2 meters in length

- ◆Complies with the international standards of IEC60914 and GBT15381-94.
- ◆Professional high-fidelity condenser microphone element, sensitive in sound pickup, clear in voice, with a bandwidth reaching 20Hz~20KHz.
- ◆Adopts an anti-interference circuit design, which can prevent interference from electronic products such as mobile phones.
- ◆The microphone head is equipped with a speaking indicator ring, which can display the speaking and closed status of the unit.
- ◆The speaking switch button has a translucent speaking pattern that stays on when speaking.
- ◆Equipped with an LED display screen.
- ◆The unit uses a T-shaped 8-core connection cable. The cable is fully shielded with aluminum foil and water wire, reducing the interference of strong electromagnetic waves on the cable.
- ◆Supports multiple chairman units. When connecting, there are no location restrictions, and they can be installed arbitrarily. It has the priority function of fully controlling the conference order and can regulate the conference atmosphere.
- ◆The "daisy chain" cable series connection mode is adopted, which is convenient for installation and maintenance.