



Frequency Range:	UHF 640-695MHz
Modulation Mode:	Wideband FM
Working Distance:	60 meter
Oscillation:	PLL syntheized
Sensitivity:	When the deviation is 25KHz and the input is 6dBv, S/N > 60Db
Bandwidth:	30MHz
Maximum deviation:	±45KHz
Comprehensive S/N ratio:	>105dB
Comprehensive T.H.D:	@1KHz < 0.7%
Power supply:	DC12V~16V

- ◆ IEC60914, GBT15381-94
- ◆ In the same environment, up to 20 sets of the system can be used simultaneously. Each set of the system can support 199 delegates or one chairman plus 198 delegates.
- ◆ It has functions such as first - in - first - out, chairman's exclusive, speech restriction, speech time limitation, and one - key shutdown. At most, 4 units are allowed to speak simultaneously.
- ◆ A 4.3 - inch touch color display screen intuitively shows and facilitates the adjustment of various parameters of the system.
- ◆ It has a video function.
- ◆ AB antenna socket: for installing audio antennas.
- ◆ C antenna socket: for installing control channel antennas.
- ◆ Parallel output: independent audio XLR parallel output.
- ◆ Non - parallel mixing output: audio 6.3 mixing output.
- ◆ RS - 232 socket: connects to a video switcher.
- ◆ RS - 232 camera interface.
- ◆ RS - 485 camera interface: when connecting a camera with a 485 interface, the corresponding A and B should be connected to the A and B of the camera.
- ◆ USB computer interface: can be connected to computer software for camera tracking or other function settings.



As the product are improving, these won't be any further notice for the improvement. Please subject to actual but not picture.