



OutputPower(4–16Ω / 70V / 100V)	120W	240W	360W	660W
THD+N	<0.1% (1kHz)			
Frequency Response	80Hz – 18kHz ±1.5dB			
Tone Control	Bass ±10dB (100Hz), Treble ±10dB (10kHz)			
Damping Factor	>300@			
Unweighted Noise	≥ -85dB			
Input Sensitivity	Line: 0dB / MIC: -20dB			
Input Impedance	Line: 20kΩ / MIC: 1kΩ			
Input Terminals	RCA (Line), 6.3mm Jack (MIC)			
Output Terminal	Screw-fixed terminal block			
Power Supply	AC180V – 260V, 50/60Hz			
Power Consumption (Max)	180W	320W	500W	800W
Dimensions (HxWxD)	Approx. 88 × 420 × 278 mm			

- **3-Channel MIC Input** — One channel with priority and adjustable voice compression
- **2 AUX Inputs** — For music source flexibility
- **Insert Input** — 1-channel priority signal input
- **USB & Bluetooth 5.0 Audio Playback**
- **2 "Ding-Dong" Prompt Tones** for paging alerts
- **16 DSP Sound Effects** for microphones
- **Bass / Treble EQ** — 100Hz ±10dB (bass), 10kHz ±10dB (treble)
- **Multi-segment LED Level Indicator**
- **Complete Protection Circuit** — DC, short circuit, overload, overheat
- **6-Zone Output Control** — RMS 100V output per zone
- **Equipped with external control mute socket**